






Model 246



PICTURE MODEL: 246-065
2-VALVE MANIFOLD FOR DIRECT MOUNTING ON ROSEMOUNT 3051
PRESSURE TRANSMITTER WITHOUT CO-PLANAR FLANGE WITH MOUNTING BRACKET

Standard materials				
Body, Bonnet	AISI 316 L			
Needle point	Rotating ceramic ball Al ₂ O ₃			
Stem	AISI 316 Ti with chromium-carbide diffusion coating			
Connections				
Process	1/2-14 NPT (F)	ANSI / ASME B1.20.1		
Instrument	Flanged			
Vent / Purge	1/4-18 NPT (F)	ANSI / ASME B1.20.1		
Instrument mounting material				
4 Bolts 7/16" UNF	AISI 316			
Stem packing	Code	P/T		Material
Teflon (PTFE)	xxx-01	413 barg 38 °C 200 barg 230 °C 6000 psig 100 °F 3000 psig 450 °F		AISI 316 (L)
VITON	xxx-06	600 barg 38 °C 200 barg 200 °C 9000 psig 100 °F 3000 psig 400 °F		AISI 316 (L)
Grafoil	xxx-05	413 barg 38 °C 200 barg 400 °C 6000 psig 100 °F 3000 psig 750 °F		AISI 316 (L)
Other packingmat.	Sillicon, Kalrez, Supagraf Premier, EPDM, Elast-o-lion			
Special alloys	Alloy 400	Alloy C-276	TITAN	DUPLEX 1.4462
Model	xxx-02	xxx-03	xxx-04	xxx-20
Stem packing	PTFE	PTFE	PTFE	VITON O-ring
	Alloy 825	Alloy 625	Alloy 254Smo (6M0)	
Model	xxx-12 (825)	xxx-12	xxx-11	Other on request
Stem packing	PTFE	PTFE	PTFE	
Optional				
Oxygen cleaned				xxx-xx/C
G-threaded connections				xxx/B -xx
All connections G-threaded ¼				xxx/B14-xx
MonelK500 (NACE compliance)				xxx-xx5
Vent ½"NPT F (standard is ¼"NPT F)				xxx/V12-xx
Mounting bracket				904, 906 or 906/P

Model 246



246-065

